




Features

- Absorbent Glass Mat (AGM) technology for superior performance
- Valve regulated, spill proof construction allows safe operation in any position
- Power/volume ratio yielding unrivaled energy density
- Rugged impact resistant ABS case and cover (UL94-HB)
- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified
- U.L. recognized under file number MH 20845


Terminals

(mm)

- T12: Threaded insert w. 5 mm stud fastener



Physical Dimensions: in (mm)




L: 6.50 (165) W: 4.92 (125) H: 6.89 (175) HT: 6.89 (175)

Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.


Performance Specifications

Nominal Voltage	12 volts (6 cells)
Nominal Capacity	
20-hr. (1.27A to 10.50 volts)	25.40 AH
10-hr. (2.40A to 10.50 volts)	24.00AH
5-hr. (4.16A to 10.20 volts)	20.82 AH
1-hr. (14.76A to 9.00 volts)	14.76 AH
15-min. (41.1A to 9.00 volts)	10.35 AH
Approximate Weight	19.2 lbs. (8.7 kg)
Energy Density (20-hr. rate)	1.38 W-h/in ³ (84.41 W-h/l)
Specific Energy (20-hr. rate)	15.88 W-h/lb (35.0 W-h/kg)
Internal Resistance (approx.)	15 milliohms
Max Discharge Current (7 Min.)	76.2 amperes
Max Short-Duration Discharge Current (10 Sec.).....	254.0 amperes
Shelf Life (% of nominal capacity at 68 °F (20 °C))	
1 Month	92%
3 Months.....	90%
6 Months	80%
Operating Temperature Range	
Charge..	-4 °F (-20 °C) to 122 °F (50 °C)
Discharge.....	-40 °F (-40 °C) to 140 °F (60 °C)
Case	ABS Plastic (UL 94-HB)
Power-Sonic Chargers	PSC-124000A-C


Discharge Characteristics




Charging Characteristics (Cycle Use)



Temperature Effects in Relation to Battery Capacity



Temperature Effects in Relation to Battery Capacity



Charging

Cycle Applications: Limit initial current to 7.6A. Charge until battery voltage (under charge) reaches 14.4 to 14.7 volts at 68°F (20°C). Hold at 14.4 to 14.7 volts until current drops to under 254mA. Battery is fully charged under these conditions, and charger should be disconnected or switched to “float” voltage.


“Float” or “Stand-By” Service: Hold battery across constant voltage source of 13.5 to 13.8 volts continuously. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition.

Note: Due to the self-discharge characteristics of this type of battery, it is imperative that they be charged within 6 months of storage, otherwise permanent loss of capacity might occur as a result of sulfation.

Chargers

Power-Sonic offers a wide range of chargers suitable for batteries up to 100AH. Please refer to the Charger Selection Guide in our specification sheets for “C-Series Switch Mode Chargers” and “Transformer Type A and F Series”. Please contact our Technical department for advice if you have difficulty in locating suitable models.

Self Discharge Characteristics



- A** No supplementary charge required
(Carry out supplementary charge before use if 100% capacity is required.)
- B** Supplementary charge required before use. Optional charging way as below:
1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
3. Charged for 8~10 hours at limited current 0.05CA.
- C** Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached

Further Information

Please refer to our website www.power-sonic.com for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc..

Contact Information



DOMESTIC SALES
Tel: (07) 3386 1102
Fax: (07) 3102 9913
sales@spb.net.au

www.sealedperformance.com.au
1 Ant Road, Yatala
Brisbane QLD 4207

